Temp-Tec 332

DESCRIPTION AND GENERAL PROPERTIES

- Material Neoprene
- Length (cm) 35.5
- Colour/Color Black / Blue
- Interior finish Knitted thermal protection
- Exterior finish Pebbled
- Size / EAN 8 9 10
- Packaging 1 pair/bag - 6 pairs/carton

PERFORMANCE RESULTS

Certification category 3

CE 0334

111

02XXXX

ACJKL

2212

Legends

EN 388 **MECHANICAL HAZARDS**

PERFORMANCE LEVELS
0-4 0-5 0-4 0-4 A-F (P)
- Abrasion resistance
- Blade cut resistance
- Tear resistance
- Puncture resistance
- Cut resistance according to ISO 13997
- Impact protection

EN 407 **THERMAL RISKS heat and fire**

PERFORMANCE LEVELS
0-4 0-4 0-4 0-4 0-4 0-4
- Burning behaviour
- Contact heat resistance
- Convective heat resistance
- Radiant heat resistant
- Resistance to small drops of molten metal
- Resistance to large quantities of molten metal

CHEMICAL RISKS

EN ISO 374-1 Type A — U V W X Y Z

EN ISO 374-1 Type B — X Y Z

EN ISO 374-1 Type C

A	Methanol	**J**	n-Heptane
B	Acetone	**K**	Sodium hydroxide 40%
C	Acetonitrile	**L**	Sulphuric acid 96%
D	Dichloromethane	**M**	Nitric acid 65%
E	Carbon Disulfide	**N**	Acetic acid 99%
F	Toluene	**O**	Ammonia 25%
G	Diethylamine	**P**	Hydrogen peroxide 30%
H	Tetrahydrofurane	**S**	Hydrofluoric acid 40%
I	Ethyl acetate	**T**	Formaldehyde 37%

ANSI A1 CUT **CUT RESISTANCE**

A1	≥ 200 G	**A4**	≥ 1500 G	**A7**	≥ 4000 G
A2	≥ 500 G	**A5**	≥ 2200 G	**A8**	≥ 5000 G
A3	≥ 1000 G	**A6**	≥ 3000 G	**A9**	≥ 6000 G

MICRO-ORGANISMS

EN ISO 374-5 **Potection against bacteria, fungi**

EN ISO 374-5 **Potection against bacteria, fungi, virus**

VIRUS

EN 511 **COLD HAZARDS**

PERFORMANCE LEVELS
0-4 0-4 0 or 1
- Convective cold resistance
- Contact cold resistance
- Water permeability

EN 421 **RADIOACTIVE CONTAMINATION**

For more details: **www.mapa-pro.com**

MAPA SPONTEX PROFESSIONNEL - Défense Ouest - 420, rue d'Estienne d'Orves - 92705 Colombes Cedex - FRANCE
Tel: +33 (0)1 49 64 22 00 - Fax: +33 (0)1 49 64 24 29

MAPA® PROFESSIONNEL
www.mapa-pro.com

Temp-Tec 332

DESCRIPTION AND GENERAL PROPERTIES

- Multi-purpose chemical resistance (acids, aliphatic solvents) increased by the thickness of the material
- Excellent thermal insulation, due to double-knit cotton
- Good grip of wet or slippery objects, due to embossed texture

MAIN FIELDS OF USE

Petrochemical industry
- Sampling of hot petrochemical products

Rubber industry
- Polymer extrusion

Other industries
- Steam cleaning
- Road works in cold conditions
- Manufacture of insulating electric wires
- Boiler room work
- Manufacture of adhesives
- Handling of moulds in the ceramic industry
- Handling of hot piping

Mechanical industry
- Chemical treatment of metals
- Oil quenching of steel

INSTRUCTIONS FOR USE

Instructions for use
- It is recommended to check that the gloves are suitable for the intended use, because the conditions of use at workplace may differ from the «CE»-type tests. For very high or low temperatures, be careful that a sustained contact does not cause burns.
- It is not recommended for persons sensitized to dithiocarbamates to use these gloves.
- Put the gloves on dry, clean hands.
- Do not use the gloves in contact with a chemical for a duration in excess of the measured breakthrough time. Refer to the website www.mapa-pro.com or contact the Technical Customer Service - MAPA PROFESSIONNEL (stc.mapaspontex@mapaspontex.fr) in order to know this breakthrough time. Use 2 pairs alternatively when in long duration contact with a solvent.
- Turn the cuff end down in order to prevent a hazardous chemical from dripping onto the arm.
- Ensure the inside of the gloves is dry before putting them on again.

Storage conditions
Store the gloves in their original packaging at a temperature not below 5°C.

Laundering conditions
Before taking off the gloves, clean them as appropriate :
-in use with paints, pigments and inks : wipe with a clean cloth dampened with a suitable solvent, and rub over with a dry cloth
- in use with a solvent (diluents, etc...) : rub over with a dry cloth
- in use with acids or alkalies : thoroughly rinse the gloves under running water, and rub over with a dry cloth

Caution : improper use of the gloves or submitting them to a cleaning or laundering process that is not specifically recommended can alter their performance levels.

LEGISLATION

This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council. This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).
- CE-Type Examination Certificate

0072/014/162/06/98/0129
- Issued by the notified body nr

0072
I.F.T.H. – av. Guy de Collongue - F-69134 ECULLY CEDEX
- Quality assurance certificat

0334 Asqual 14 rue des Reculettes -F-75013 PARIS

MAPA®
PROFESSIONNEL
www.mapa-pro.com